



# **The Borough of Beaver**

## **Public Roadway Access Permit Agreement**

The Applicant/Contractor agrees to cover the public roadway if an excavation is exposed for longer than 24 hours. The Applicant/Contractor agrees that any additional fees incurred as a result of this opening will be payable to Beaver Borough within five (5) working day or the fees incurred will be deducted from the bond. For any utility inspection, the Applicant/Contractor agrees the bond will be redeemed in the event the contractor fails to have a proper inspection completed.

The intent of this permit is to provide contractor approval to gain access to public streets/alleys, sidewalks, curbs, and utilities located within the Beaver Borough right of way. By applying for this permit, the contractor agrees to save the Borough, it's officers, engineers, police, and employees harmless from all costs, damages, and liabilities which may accrue or be claimed to accrue by reason of such work performed is said permit.

## **The Borough of Beaver**

### **Public Roadway Access Permit Guidelines**

1. Contractor must obtain and maintain Public Roadway Access Permit on side during work. Failure to furnish permit will result in the issuance of a Stop Work Order by the Borough manager or Designee.
2. All excavation in the roadway must be backfilled with 2A Limestone. Excavated material must be hauled away.
3. Street must be saw cut a minimum of 12 inches beyond the original ditch or hole in a square or rectangular shape.
4. **Contractor must contact Beaver Borough to inspect the excavated site in advance of placement of backfill material.**
5. The backfill and pavement re-construction is to be in accordance with the attached "Flexible Pavement Restoration" except as departures have been authorized by the appropriate Beaver Borough officials.
6. Brick streets follow the same procedure with the following exception:
  - a. Bricks must be placed on either 6" of bituminous binder or 4" of concrete base.
  - b. No saw cutting.
  - c. Binder/concrete patch to extend 12" beyond original hole.

## **The Borough of Beaver**

### **Water/Sewer Line Permit Guidelines**

#### **Sewer Line Services**

1. Service line material from the property to the main sewer line shall be extra strength vitrified clay pipe conforming to ASTM specification C-200, 4 inch diameter or plastic schedule 40 or equivalent, 4 inch diameter. The diameter of the pipe shall not be smaller than 4 inches.
2. Pipe shall be installed with a minimum slope of 1/4 inch per foot and a minimum cover of 2 1/2 feet.
3. The Borough shall be given 24 hours notice prior to connection or tapping to inspect and approved the work of the connection.
4. The Borough shall be present at the time the contractor proposes to reconnect or tap into the system.
5. All connections to the sanitary sewer system shall be for the purposes of wastewater only. No connection is approved for roof drain water, storm water, spring water, or surface water.

#### **Water Line Services**

1. Service line material extending from water main shall be type K soft copper or 200 PSI Plastic.
2. The Borough shall be given 24 hours notice prior to connection or tapping to inspect and approved the work of the connection.
3. The Borough shall be present at the time the contractor proposes to or tap into the system.
4. Repairs between the curb box and property must be made with soft copper or 200 PSI Plastic.
5. Repairs between the curb box and the water main must be made with soft copper, repairs on materials not plastic or copper.
6. The Borough shall furnish a corporation stop and the corundum key stop at cost.